

## L21 (linear lighting fixture, recessed, with trim and trimless)



### Features

simple design, comfortable performance

### Finishing


Anodizing, silver gray,  
white, black, etc.,  
according to customers' color specimen.

### Applications

Commercial / Retail / Shops/Office/others

### Accessories

End caps (aluminum die-casting),  
mounting kits, blank parts,  
straight connector, L, T & + shape connectors




### Other specs

\*IP20 rated    \*Products could be sold as materials non-assembled


\*Linear system lengths @ any customers' demand, with either shadow-free solution or blank parts


### Connections



### Warranty


2 years for fixtures excluding light source and gears






**Connection:**

90 degree connection:



straight connection:



**Specs for LED:** (take recessed with trim for example)

(CRI: 80 above, optional color temperatures: 3000k/4000k/5000k/6000k)

Size (mm)	system wattage (w)	system lumen output (lm)
612*(95/112)*80	11.60w	812lm @ constant driving current 350mA
612*(95/112)*80	23.20w	1624lm @ constant driving current 350mA
912*(95/112)*80	17.40w	1218lm @ constant driving current 350mA
912*(95/112)*80	34.80w	2436lm @ constant driving current 350mA
1212*(95/112)*80	23.20w	1624lm @ constant driving current 350mA
1212*(95/112)*80	46.40w	3248lm @ constant driving current 350mA
1512*(95/112)*80	29.00w	2030lm @ constant driving current 350mA
1512*(95/112)*80	58.00w	4060lm @ constant driving current 350mA


**Specs for T5 tubes:** (take recessed with trim for example)

Size (mm)	system wattage (w)	remark
612*(95/112)*80	1*14w/2*14w	T5 version
912*(95/112)*80	1*21w/2*21w	T5 version
1212*(95/112)*80	1*28w/2*28w	T5 version
1512*(95/112)*80	1*35w/2*35w	T5 version

**Cutout sizes @ the ceiling**

Recessed with trim		Recessed TRIMLESS	
Fitting sizes(mm)	cutout hole size(mm)	Fitting sizes (mm)	cutout hole size (mm)
612*(95/112)*80	602*100	600*95*80	600*95
912*(95/112)*80	902*100	900*95*80	900*95
1212*(95/112)*80	1202*100	1200*95*80	1200*95
1512*(95/112)*80	1502*100	1500*95*80	1500*95



Optional diffusers for T5 tubes version:



How to achieve the shadow-free solution by adoption of T5 tubes?

T5 tubes overlapped at reasonable distance.

See below



**Please contact us, in case you need customize other linear lighting fixtures**