BY ESTELLES LIGHTING

4000K

Intertek

3000К

Dimensions

LINKABLE LINEAR SERIES

IL-LED015-Up/Down



6000К

MAX 59.1"(5ft) 1500mm .9" 23.5mm

36.6"(3.1ft) 60.2"(5ft)

24.8"(2.1ft) 48.4"(4ft)

Catalog # TypeTypeProjectCommentsDatePrepared by

Description

Choose the type of light you need by selecting your ideal color temperature during the installation of this LED suspension light fixture. This selectable fixture features a switch that can adjust the color temperatures of the light the fixture emits.

Designed to make a statement, this minimalistic linear LED connects with other 3 ft., 4 ft., or 5 ft. linear pendants using a line joiner to create a continuous run of light. Its deep regressed lens evenly distributes glare-free light that is easy on the eyes for longer day-to-day use.

Replace existing fluorescent strip fixtures with this more efficient color selectable LED suspension light fixture to reduce energy and maintenance costs.

Product Specification	
Mode	IL-LED015-Up/Down
ССТ	3000K, 4000K,6000K
Wattages	30W, 40W
Lumens	2880lm, 3605lm
Input Voltage	100-277V
Power Factor	>0.95
Dimming	Non-Dimmable/ 0- 10V
CRI	≥ 80, ≥ 90
Finishes	White, Black, Grey, Custom
Beam angle	360°
IP	IP20
Dimensions	L: 3ft,4ft,5ft, W: 4.0" x H: 0.9"
Application	Suspended
Llfespan	50,000+ Hours
Certification	ETL Listed
Warranty	5 years

ORDERING INFORMATION

ITEM NUMBER	Lengths	Wattages/ft	Input Voltage	ССТ	Dimming	Finish
IL-LED015-Up/Down 3ft 4ft 5ft	3ft	30W	00-277V	3000K	Non Dimmable	White
	4ft	40W		4000K	0 -10V (integrated)	Black
	5ft	40W		6000K	DALI (integrated)	Grey
					TRIAC (integrated)	Custom

www.impulselightingusa.com

Due to continuous improvements, the information herein may be changed without notice

Impulse Lighting Inc.

12603 FM 529 Rd Houston TX Phone: 855-315-3651