



Description

- Aluminum die casting cover, extruded aluminum body, it can be cut different height.
- High transparent PC diffuser, it can effectively prevent yellowing and aging.
- Indirect light luminaire for use with led, which has high visual comfortable.
- High quality LED chips, Driver with 0-10V/DALI/programmed options.
- Surface anti-ultraviolet pure polyester powder painting.
- The maximum surface temperature of all accessible part under 122°F.
- **Other Options:** Move sensor options / Emergency options / Color temperature options

Photometric Data





EL -C-13B



EL -C-13BS

Dimensions



Dimensions
6.6" Dia x 31"H
6.6" Dia x 39"H

Ordering Info:

Model	Watts	Lumens	Sizes (H)	Color Temperature	Finishes	Distribution	Accessories (Order Separately)
EL-C-13 EL-C-13A	25W	2225lm	31" 39"	30 - 3000K 4K - 4000K	Black Matt Silver	R0 - 360°	ABAAnchor-Anchor Bolt Kit

PRODUCT SPECIFICATIONS

Housing	Aluminum
---------	----------

Lens	Polycarbonate Lens
------	--------------------

Finish	Black, Matt Silver
--------	--------------------

Environmental system

Work environment	Suitable for Wet Locations
------------------	----------------------------

Operating temperature	-30°F to 122°F (-30°C to 50°C)
-----------------------	--------------------------------

L-70 Life	> 50,000 hrs
-----------	--------------

Electrical system

Input voltage	120V
---------------	------

CRI	≥ 80
-----	------

IK Rating	IK09
-----------	------

Light source type	LED
-------------------	-----

IP	IP66
----	------

Lumens	2225lm
--------	--------

Power consumption	25W
-------------------	-----

Certifications	cETLus certified
----------------	------------------

Warranty	5-year limited
----------	----------------