



Description

LED SWIVEL HARDSCAPE LIGHT WITH RGBW has 12V low-voltage design ensuring its safety when used outdoors (transformer is not included). Swivel light head allows you to adjust the illumination angle from 0-90 degree. The PC lens with a 115° beam angle grants you even light distribution. HUB for group control via Wi-Fi is included.

RGBW - The fixture has RGBW design with APP control. You can easily select Red, Green, Blue, White (2,700K-6,500K) colors or its' combinations, having 16.7 million colors in total. You can also choose lighting patterns and set up a schedule, having a great variety of good looking effects. All of it is easily controlled by Smart APP on your Smartphone. The fixture is also compatible with Alexa and Google Assistant.

CUTTABLE DESIGN - Mounting plate's width can be adjusted by cutting it along the dotted line according to your needs.

APPLICATION - This fixture is rated for Wet Locations. It is perfect for mounting between hardscapes like retaining walls, barbecue fire pits, bricks, landscape steps, masonry walls, etc.

ADVANTAGES - With a lifespan of 50,000 hours, these fixtures are made to last decades under normal operation! Estelle's provides a 5-year limited warranty along with ETL certification to guarantee top quality products and safety



Ordering Info:

Model	Size	Watts	Voltage	Lumens	CCT	Finish
EL-HSLS4-2SM-RGBW-BR	4" 7" 12"	1.5W 3W 5W	12V	50lm 107lm 159lm	Red Green Blue 2700K-6500K	Bronze

PRODUCT SPECIFICATIONS

Housing	Aluminum
Lens	Acrylic
Finish	Bronze
Environmental system	
Work environment	Suitable for Wet Locations
Operating temperature	-40°F to 113°F (-40°C to 45°C)
L-70 Life	> 50,000 hrs
Optical system	
Color temperature	from Red-Green-Blue-2,700K-6,500 K with smart app
CRI	> 80
Electrical system	
Input voltage	12V
Max input current	0.87 A / 1.67 A / 0.15 A
Inrush current (Action time)	0.25 A (20 S
Power consumption	1.5W / 3W / 5W
Power factor	> 0.9
Certifications	ETL certified
Warranty	5-year limited

INSTALLATION GUIDE

IMPORTANT SAFETY INFORMATION:

Please read all the instructions below before installation.

- Make sure that the supply voltage corresponds to the rated product voltage.
- The product must be installed by a qualified electrician in accordance with the National Electrical Code and corresponding local codes.
- If the product is damaged, do not use it.

WARNING

RISK OF PERSONAL INJURY – READ and follow all WARNINGS and installation instructions. Keep or give to the owner for future reference. Risk of cuts: Wear gloves to prevent cuts or abrasions when removing from carton, handling, installing, and maintaining this product. Risk of electric shock: This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved. Risk of Fire: Minimum 194°F supply conductors. Consult a qualified electrician to ensure correct branch circuit conductor. Estelle's assumes no responsibility for claims arising out of improper or careless Installation or handling of this product.

INSTALLATION STEPS:

1. Unscrew the two fixture screws from both sides of the wall sconce. Remove the mounting plate and attach it to the existing outlet box using two mounting screws.
2. Choose preferred color temperature on the back side of the fixture by adjusting switch position. Connect the wires: Black to Black, White to White, Ground to Ground. Secure the connection with wire nuts.
3. Fix the wall sconce to the mounting plate using two fixture screws on both sides. Before tightening the screws, align the holes of both the fixture and the mounting plate to ensure a solid fit.

