



				
2700K	3000K	3500K	4000K	5000K

Dimming

Universal dimming driver (TRIAC and 0- 10V)

Finish

Offered in black, silver, white and bronze finishes

Electrical

Selectable power, Input 120V-277VAC 50/ 60Hz

Minimum starting temp -4° F/-20° C

LED

Integrated LED modules capable of producing:

Selectable CCT: 2700K 3000K 3500K 4000K 5000K 90 CRI for 50,000 Hrs.

MOUNTING

Over a 3" 4" or 5" octagonal j-box

Certification

All fixtures are ETL cETLus FCC for outdoor wet locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Catalog #	Type	Type
Project		
Comments		Date
Prepared by		

FEATURES

Luker series wall cylinders are ideal for a wide variety of interior and exterior applications including residential and commercial. The aluminum cylinders offer a contemporary design with their sleek cylindrical form. Their elegant fade and chip resistant finish which is available in Antique Black, Silver, Bronze, and White is perfect for inspired exteriors.

Die-Cast Aluminum

Made of a the sturdy die-cast aluminum frame in 4 finishes, this weather resistant wall light fixture is suitable for wet locations and exposure to direct sunlight

Power	15W, 20W, 25W, 30W
CCT	2700K, 3000K, 3500K, 4000K, 5000K
Input:	120 VAC, 50/60Hz
Dimming	ELV: 100-10%
Light Source	Integrated LED
Lens	Glass Lens
Rated Life	50000 Hours
Standards	ETL, cETL, Wet Location Listed

ORDERING INFORMATION

ITEM NUMBER	Wattages	Color Temp	CRI	Lumens	Up & Down	Optional
IL-CYR-30W	15W	2700K	≥ 90	1350lm	7.5W*7.5W	Emergency Back up Emergency or Photocell 45° / 80°
	20W	3000K		1800lm	10W*10W	
	25W	3500K		2250lm	12.5W*12.5W	
	30W	4000K		2700lm	15W*15W	
		5000K				

DIMENSIONS

