Product: **EL-2002D SERIES | LED BOLLARD LIGHT | CONCRETE TEXTURED FINISH**

Project Name

SPECIFICATION SHEET



PRODUCT OVERVIEW

The EL-2002D LED bollard features a cylindrical aluminum housing with a concrete textured finish and a louvered light head. Designed for fixed outdoor installation, it provides 90° light distribution with three wattage options.

KEY FEATURES

- Aluminum housing with concrete textured finish
- Louvered cylindrical design
- 10W / 18W / 25W options
- 3000K / 4000K / 5000K color temperature options
- 120–277V input
- 3-in-1 dimming: 0–10V / PWM / Resistance
- IP65 rated
- 40,000-hour rated life
- 5-year warranty

AVAILABLE FINISHES

Concrete Textured

UL LISTED

WET LOCATION

GENERAL SPECIFICATIONS

Specification	Details
Product Code	EL-2002D
Fixture Type	LED Bollard
LED Brand / Type	LUXEON 5050
LED Quantity	16 × 2
Input Voltage	120–277V AC
Frequency	50/60Hz
Wattage Options	10W / 18W / 25W
Color Temperature Options	3000K / 4000K / 5000K
Color Rendering Index	70 CRI
Beam Angle	90°
Power Factor	>0.9
Dimming	0–10V / PWM / Resistance
IP Rating	IP65
Housing Material	Aluminum
Finish	Concrete Textured
Installation	Fixed Mount
Operating Temperature	−40°C to 50°C / −40°F to 122°F
Rated Life	40,000 Hours
Warranty	5 Years

Product: **2002D SERIES | LED BOLLARD LIGHT | CONCRETE TEXTURED FINISH**

Project Name

ORDERING INFORMATION			
Proposed example: 2002D-18W-40K-CT			
Series	Wattage	Color Temperature	Finish
EL-2002D	10W 18W 25W	30K — 3000K 40K — 4000K 50K — 5000K	CT — Concrete Textured

LIGHT OUTPUT			
Color Temperature	**10W**	**18W**	**25W**
3000K	481.61 lm	851.30 lm	1,088.28 lm
4000K	483.49 lm	884.41 lm	1,115.25 lm
5000K	474.93 lm	854.27 lm	1,075.66 lm

DIMENSIONS		
Dimension	**Millimeters**	**Inches**
Diameter	160 mm	6.30″
Overall Height	695 mm	27.36″

